

# Cisco IOSによるENUMデモ

シスコシステムズ株式会社

アライアンスアンドテクノロジー

先進ソリューション開発部

岩岸 優希

[yiwagish@cisco.com](mailto:yiwagish@cisco.com)

# ENUM対応製品

Cisco.com

音声Gateway(ルータ)


-Cisco IOS ソフトウェア 12.2(11)T以降

Proxyサーバ


-Cisco SIP Proxy Server

# ENUM デモ 03/10/23

Cisco.com




# ENUM デモ 04/5/12



# ENUM デモ 04/5/12

Cisco.com



# 機器構成

Cisco.com

- **Voice Gateway @シスコ新宿オフィス**

**Cisco 3725**

**-NM-2V**

**-VIC-2BRI-S/T-TE**

**-IOS 12.3(7)T1**

- **Cisco CallManager Express @早稲田大学**

**Cisco 1751**

**-IOS 12.3(7)T1**

**Cisco Wireless IP Phone 7920**

**Cisco Aironet 1200**

**Catalyst 2940**

# ENUM – Voice Gateway

Cisco.com

```
ip name-server
call application voice default disc-prog-ind-at-connect 1
isdn switch-type ntt
voice enum-match-table 1
rule 1 1 /^¥(.*)¥/ ¥1/ e164.jp
interface FastEthernet0/0
ip address
duplex auto
speed auto
interface BRI1/0
no ip address
isdn switch-type ntt
isdn incoming-voice voice
isdn calling-number
dial-peer voice 10 voip
destination-pattern 813.....
session protocol sipv2
session target enum:1
codec g711ulaw
sip-ua
```

# ENUM – CallManager Express


Cisco.com

```
ip name-server
voice enum-match-table 1
rule 1 1 /^¥(.*)¥/ ¥1/ e164.jp
interface Ethernet0/0
ip address Global IP
interface FastEthernet0/0
ip address 192.168.0.254 255.255.255.0
dial-peer voice 10 voip
destination-pattern 813.....
session protocol sipv2
session target enum:1
dial-peer voice 2 voip
session protocol sipv2
incoming called-number 2000
telephony-service
max-phones 2
max-dn 2
ip source-address 192.168.0.254 port 2000
ephone-dn 1 dual-line
number 2000
ephone 1
mac-address 000D.282E.78A6
type 7920
button 1:1
sip-ua
```

# Cisco CallManager and CallManager Express

Cisco.com

SMB Office A



# CISCO SYSTEMS



EMPOWERING THE  
INTERNET GENERATION